

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 2
光源	L L D 2 0 0 0 L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 6 5 8 (1) D R 1
B Z 分類	B Z 1

器具効率		5 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	4 3	3 9	3 6	3 5	4 2	3 9	3 6	3 5	4 2	3 8	3 6	3 5	4 1	3 8	3 6	3 4	3 4
			0 . 6 3	0 . 8	4 7	4 3	4 1	3 9	4 6	4 3	4 1	3 9	4 5	4 3	4 1	3 9	4 5	4 2	4 0	3 9	3 8
			0 . 5 6	1 . 0	4 9	4 6	4 4	4 2	4 9	4 6	4 4	4 2	4 8	4 5	4 4	4 2	4 7	4 5	4 3	4 2	4 1
				1 . 2 5	5 1	4 9	4 7	4 5	5 1	4 8	4 6	4 5	5 0	4 8	4 6	4 5	4 9	4 7	4 6	4 4	4 4
下方投影面積		c m ²	1 . 5	5 3	5 0	4 8	4 7	5 2	5 0	4 8	4 7	5 1	4 9	4 8	4 6	5 0	4 8	4 7	4 6	4 5	
			等価発光面積	c m ²	2 . 0	5 4	5 2	5 1	5 0	5 4	5 2	5 1	4 9	5 3	5 1	5 0	4 9	5 2	5 0	4 9	4 8
取付高さ	器具間隔最大限		2 . 5	5 5	5 4	5 2	5 1	5 5	5 3	5 2	5 1	5 4	5 2	5 1	5 0	5 2	5 1	5 1	5 0	4 9	
	横方向 (A) 縦方向 (B)		3 . 0	5 6	5 5	5 3	5 2	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 1	5 0	
H m	0 . 6 4 H m	0 . 6 4 H m	4 . 0	5 7	5 6	5 5	5 4	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 3	5 4	5 3	5 3	5 2	5 1	
			5 . 0	5 7	5 6	5 5	5 5	5 7	5 6	5 5	5 4	5 5	5 5	5 4	5 4	5 4	5 4	5 3	5 3	5 1	
			7 . 0	5 8	5 7	5 6	5 6	5 7	5 6	5 6	5 5	5 6	5 5	5 5	5 4	5 5	5 4	5 4	5 4	5 2	
			1 0 . 0	5 8	5 8	5 7	5 7	5 7	5 7	5 7	5 6	5 6	5 6	5 6	5 5	5 5	5 5	5 5	5 4	5 3	

