

屋内照明器具特性	
品番 (品名)	LGBZ2805K
光源	LED6200_70_4700 x1 4700.0lm
管理番号	K0147884(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	13%	床	10%				10%				10%				10%				0%	
下方光束	87%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	53	41	33	28	51	40	32	27	48	38	31	26	44	36	30	26	23	
		0.8	63	51	43	37	61	50	42	37	56	47	40	35	52	45	39	34	31	
		1.0	69	58	50	44	67	57	49	44	62	54	47	42	58	51	45	41	37	
		1.25	75	65	57	51	73	63	56	51	68	60	54	49	63	56	51	47	43	
下方投影面積	cm ²	1.5	79	70	63	57	77	68	61	56	71	64	59	54	67	61	56	52	47	
		2.0	85	77	70	65	82	75	69	64	77	71	66	61	72	67	63	59	54	
取付高さ	器具間隔最大限		2.5	88	82	76	71	86	79	74	69	80	75	71	67	75	71	67	64	59
	横方向 (A)	縦方向 (B)	3.0	91	85	80	75	88	83	78	74	83	78	74	71	78	74	71	68	62
1.5m	1.99m	1.99m	4.0	94	89	85	81	91	87	83	79	86	82	79	76	81	78	75	73	67
2	2.62	2.62	5.0	96	92	88	85	93	90	86	83	88	85	82	79	83	81	78	76	70
2.5	3.2	3.2	7.0	99	95	93	90	96	93	90	88	91	88	86	84	86	84	82	80	74
3	3.84	3.84	10.0	101	98	96	94	98	96	94	92	93	91	89	87	88	86	85	83	77

