

屋内照明器具特性	
品番 (品名)	LGB16702
光源	LLD2020MLCB1 ×1 460.0 lm
管理番号	K0175668 (1) DR1
BZ分類	BZ1

器具効率		8 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		8 4 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束																					
保守率		良 中 否	0 . 6 7	0 . 6	7 4	7 0	6 7	6 5	7 3	6 9	6 7	6 5	7 2	6 9	6 7	6 5	7 1	6 8	6 6	6 5	6 4
			0 . 6 3	0 . 8	7 8	7 4	7 2	7 0	7 7	7 4	7 2	7 0	7 6	7 3	7 1	7 0	7 5	7 3	7 1	6 9	6 9
			0 . 5 6	1 . 0	8 1	7 7	7 5	7 3	8 0	7 7	7 5	7 3	7 9	7 6	7 4	7 3	7 8	7 5	7 4	7 2	7 1
				1 . 2 5	8 3	8 0	7 8	7 6	8 2	7 9	7 7	7 6	8 1	7 8	7 7	7 5	7 9	7 8	7 6	7 5	7 4
下方投影面積		c m ²	1 . 5	8 4	8 1	7 9	7 8	8 3	8 1	7 9	7 7	8 2	8 0	7 8	7 7	8 1	7 9	7 8	7 6	7 5	
等価発光面積			c m ²	2 . 0	8 6	8 4	8 2	8 0	8 5	8 3	8 1	8 0	8 3	8 2	8 0	7 9	8 2	8 1	8 0	7 9	7 7
取付高さ				2 . 5	8 7	8 5	8 3	8 2	8 6	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 3	8 2	8 1	8 0	7 8
H m		器具間隔最大限		3 . 0	8 7	8 6	8 4	8 3	8 6	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 2	8 1	7 9	
0 . 4 7 H m		縦方向 (B)		4 . 0	8 8	8 7	8 6	8 5	8 7	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 4	8 3	8 3	8 2	
				5 . 0	8 8	8 7	8 6	8 5	8 7	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 4	8 3	8 3	8 1	
				7 . 0	8 9	8 8	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 4	8 3	8 3	8 1	
				1 0 . 0	9 0	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 6	8 5	8 5	8 5	8 4	8 4	8 4	8 2	

