

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 3
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 7 6 4 (0) D R 1
B Z 分類	B Z 1

器具効率		2 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
				室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	2 5	2 4	2 3	2 3	2 5	2 4	2 3	2 3	2 4	2 4	2 3	2 3	2 4	2 3	2 3	2 3	2 2	
			0 . 6 3	0 . 8	2 6	2 5	2 4	2 4	2 5	2 5	2 4	2 4	2 5	2 4	2 4	2 4	2 5	2 4	2 4	2 4	2 4	2 3
			1 . 0	2 6	2 5	2 5	2 4	2 6	2 5	2 5	2 4	2 6	2 5	2 5	2 4	2 5	2 5	2 5	2 4	2 4		
			0 . 5 6	1 . 2 5	2 7	2 6	2 5	2 5	2 6	2 6	2 5	2 5	2 6	2 6	2 5	2 5	2 6	2 5	2 5	2 5	2 5	2 4
下方投影面積		c m ²	1 . 5	2 7	2 6	2 6	2 5	2 7	2 6	2 6	2 5	2 6	2 6	2 6	2 5	2 6	2 6	2 5	2 5	2 5		
			2 . 0	2 7	2 7	2 6	2 6	2 7	2 7	2 6	2 6	2 7	2 6	2 6	2 6	2 6	2 6	2 6	2 6	2 5	2 5	
取付 高さ	器具間隔最大限		2 . 5	2 8	2 7	2 7	2 6	2 7	2 7	2 7	2 6	2 7	2 7	2 6	2 6	2 6	2 6	2 6	2 6	2 5		
	横方向 (A) 縦方向 (B)		3 . 0	2 8	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 6	2 6	2 7	2 6	2 6	2 6	2 5		
H m	0 . 7 6 H m 0 . 7 6 H m		4 . 0	2 8	2 8	2 7	2 7	2 8	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 6	2 6	2 6		
			5 . 0	2 8	2 8	2 8	2 7	2 8	2 8	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 6	2 6		
			7 . 0	2 8	2 8	2 8	2 8	2 8	2 8	2 8	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7		
			1 0 . 0	2 8	2 8	2 8	2 8	2 8	2 8	2 8	2 8	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7	2 7		

