

屋内照明器具特性

品番 (品名)	XNW0661WN				
光源	LED5000_85_560	x1	560.0	lm	
管理番号	K0164321(0)DB1				
BZ分類	BZ1				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		壁	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.81	0.6	73	65	59	55	72	64	59	55	70	63	59	55	69	63	58	55	54	
	中	0.77	0.8	82	75	70	66	81	74	69	66	79	73	69	66	78	72	68	65	64	
	否	0.68	1.0	88	81	77	73	87	81	76	73	85	79	76	72	83	78	75	72	71	
			1.25	92	87	82	79	91	86	82	79	89	85	81	78	87	83	80	78	76	
下方投影面積			1.5	95	90	86	83	94	89	86	83	92	88	85	82	90	86	84	81	80	
			2.0	99	95	91	88	97	94	91	88	95	92	89	87	93	91	88	86	84	
取付高さ	器具間隔最大限		2.5	101	97	94	92	100	96	94	92	97	95	92	90	95	93	91	90	87	
	横方向 (A)	縦方向 (B)	3.0	102	99	97	94	101	98	96	94	99	96	94	93	97	95	93	92	89	
Hm	1.26Hm	1.26Hm	4.0	104	102	99	98	103	101	99	97	100	99	97	96	98	97	96	94	92	
			5.0	105	103	101	100	104	102	100	99	101	100	99	97	99	98	97	96	94	
			7.0	106	105	103	102	105	103	102	101	102	101	100	100	100	99	99	98	95	
			10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	100	99	97	97	

