

| | |
|----------|----------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | L G W C 8 5 0 2 1 B F |
| 光源 | LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m |
| 管理番号 | K0122872(1)DB1 |
| BZ分類 | BZ10 |

| | | | | | | | | | | | | | | | | | | | |
|--------|------------------------------------|----------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|
| 器具効率 | 39% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 上方光束 | 21% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 下方光束 | 18% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 中 否 0.63 0.6 0.56 | 0.6 | 17 | 12 | 8 | 6 | 15 | 10 | 8 | 6 | 12 | 8 | 6 | 4 | 9 | 6 | 5 | 3 | 1 |
| | | 0.8 | 20 | 15 | 11 | 9 | 18 | 13 | 10 | 8 | 14 | 11 | 8 | 7 | 11 | 8 | 6 | 5 | 2 |
| | | 1.0 | 22 | 17 | 14 | 11 | 20 | 16 | 13 | 10 | 16 | 13 | 10 | 8 | 12 | 10 | 8 | 6 | 3 |
| | | 1.25 | 24 | 20 | 16 | 14 | 22 | 18 | 15 | 12 | 18 | 15 | 12 | 10 | 14 | 11 | 9 | 8 | 4 |
| 下方投影面積 | c m ² | 1.5 | 26 | 22 | 18 | 16 | 23 | 20 | 17 | 14 | 19 | 16 | 14 | 12 | 15 | 13 | 11 | 9 | 5 |
| | | 2.0 | 28 | 24 | 21 | 19 | 26 | 22 | 19 | 17 | 21 | 18 | 16 | 14 | 16 | 14 | 13 | 11 | 6 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 30 | 26 | 23 | 21 | 27 | 24 | 21 | 19 | 22 | 20 | 18 | 16 | 17 | 16 | 14 | 8 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 31 | 28 | 25 | 23 | 28 | 25 | 23 | 21 | 23 | 21 | 19 | 17 | 18 | 17 | 15 | 9 |
| H m | 0.00 H m | 2.18 H m | 4.0 | 32 | 30 | 27 | 25 | 29 | 27 | 25 | 23 | 24 | 22 | 21 | 19 | 19 | 18 | 17 | 10 |
| | | | 5.0 | 33 | 31 | 29 | 27 | 30 | 28 | 27 | 25 | 25 | 24 | 22 | 21 | 20 | 19 | 18 | 17 |
| | | | 7.0 | 34 | 32 | 31 | 29 | 31 | 30 | 28 | 27 | 26 | 25 | 24 | 23 | 21 | 20 | 19 | 12 |
| | | | 10.0 | 35 | 34 | 32 | 31 | 32 | 31 | 30 | 29 | 27 | 26 | 25 | 24 | 22 | 21 | 20 | 14 |

