

屋内照明器具特性

品番 (品名)	L G W C 8 5 0 4 4 W Z									
光源	LDA4L - H - E17 / E / S / W / 2 ×1					440.0 1 m				
管理番号	K0125233 (1) DB 1									
BZ分類	BZ4 / 0.7 / BZ5									

器具効率	77 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		9 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		68 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	59	52	46	41	57	50	45	41	54	48	43	39	50	45	41	38	35	
	等価発光面積	c m ²		1.5	62	55	50	45	60	54	49	45	56	51	47	43	53	48	45	42	38
取付高さ		器具間隔最大限		2.5	69	64	59	55	67	62	58	54	63	59	55	52	59	56	53	50	46
	H m	横方向 (A)	縦方向 (B)	3.0	71	66	62	58	69	64	61	57	65	61	58	55	61	58	55	53	49
1.14 H m		1.16 H m	4.0	73	69	66	63	71	68	64	62	67	64	61	59	63	61	59	57	53	
			5.0	75	71	68	66	73	70	67	64	69	66	64	62	65	63	61	59	55	
			7.0	76	74	72	69	74	72	70	68	70	69	67	65	67	65	64	62	58	
			10.0	78	76	74	73	76	74	73	71	72	71	69	68	68	67	66	65	60	

