

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 3
光源	L L D 3 0 2 0 L C E 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 5 7 5 8 (0) D R 1
B Z 分類	B Z 1

器具効率		7 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		7 4 %																				
保守率		良	0 . 6 7	0 . 6	6 6	6 3	6 0	5 9	6 6	6 2	6 0	5 9	6 5	6 2	6 0	5 9	6 4	6 2	6 0	5 8	5 8	
		中	0 . 6 3	0 . 8	7 0	6 7	6 4	6 3	6 9	6 6	6 4	6 3	6 8	6 6	6 4	6 3	6 7	6 5	6 4	6 2	6 2	
		否	0 . 5 6	1 . 0	7 2	6 9	6 7	6 5	7 1	6 9	6 7	6 5	7 0	6 8	6 6	6 5	6 9	6 7	6 6	6 5	6 4	
				1 . 2 5	7 4	7 1	6 9	6 8	7 3	7 1	6 9	6 8	7 2	7 0	6 8	6 7	7 1	6 9	6 8	6 7	6 6	
下方投影面積		c m ²	1 . 5	7 5	7 2	7 1	6 9	7 4	7 2	7 0	6 9	7 3	7 1	7 0	6 9	7 2	7 0	6 9	6 8	6 7		
			2 . 0	7 6	7 4	7 3	7 2	7 5	7 4	7 2	7 1	7 4	7 3	7 2	7 1	7 3	7 2	7 1	7 0	6 9		
取付 高さ	器具間隔最大限		2 . 5	7 7	7 5	7 4	7 3	7 6	7 5	7 4	7 3	7 5	7 4	7 3	7 2	7 4	7 3	7 2	7 1	7 0		
	横方向 (A)	縦方向 (B)	3 . 0	7 7	7 6	7 5	7 4	7 7	7 6	7 5	7 4	7 5	7 4	7 3	7 3	7 4	7 3	7 2	7 2	7 0		
H m	0 . 4 2 H m	0 . 4 2 H m	4 . 0	7 8	7 7	7 6	7 5	7 7	7 6	7 6	7 5	7 6	7 5	7 4	7 4	7 5	7 4	7 3	7 3	7 1		
			5 . 0	7 9	7 8	7 7	7 6	7 8	7 7	7 6	7 6	7 6	7 6	7 5	7 5	7 5	7 4	7 4	7 3	7 2		
			7 . 0	7 9	7 8	7 8	7 7	7 8	7 8	7 7	7 7	7 7	7 6	7 6	7 5	7 5	7 5	7 5	7 4	7 2		
			1 0 . 0	7 9	7 9	7 9	7 8	7 9	7 8	7 8	7 7	7 7	7 7	7 6	7 6	7 5	7 5	7 5	7 5	7 3		

