

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 5 B F
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 1 m
管理番号	K 0 1 2 5 9 7 2 (1) D B 1
B Z 分類	B Z 1 0 / 1 . 4 / B Z 9

器具効率	23 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	10 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	13 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X 0 . 0 1)																Z C M	
保守率	良	0.63	0.6	10	7	5	3	9	6	4	3	7	5	4	2	6	4	3	2	1
	中	0.6	0.8	11	8	6	5	10	8	6	5	9	6	5	4	7	5	4	3	2
	否	0.56	1.0	13	10	8	6	12	9	7	6	10	8	6	5	8	6	5	4	2
			1.25	14	11	9	8	13	10	9	7	11	9	7	6	9	7	6	5	3
下方投影面積		cm ²	1.5	15	12	10	9	14	11	10	8	11	10	8	7	9	8	7	6	4
等価発光面積		cm ²	2.0	16	14	12	11	15	13	11	10	13	11	10	9	10	9	8	7	5
取付高さ	器具間隔最大限		2.5	17	15	14	12	16	14	13	11	13	12	11	10	11	10	9	8	6
	横方向 (A)	縦方向 (B)	3.0	18	16	15	13	17	15	14	12	14	13	12	11	12	11	10	9	6
H m	1.34 H m	0.00 H m	4.0	19	17	16	15	17	16	15	14	15	14	13	12	12	11	11	10	7
			5.0	19	18	17	16	18	17	16	15	15	14	14	13	13	12	11	11	8
			7.0	20	19	18	17	19	18	17	16	16	15	15	14	13	13	12	12	9
			10.0	21	20	19	18	19	18	18	17	17	16	15	15	14	14	13	13	10

