

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 3
光源	L L D 2 0 2 0 C U 1 × 1 4 6 8 . 0 l m
管理番号	K 0 1 7 9 0 9 2 (0) D R 1
B Z 分類	B Z 1

器具効率		8 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	7 5	7 1	6 9	6 7	7 4	7 1	6 9	6 7	7 3	7 1	6 9	6 7	7 3	7 0	6 8	6 7	6 6
			0 . 6 3	0 . 8	7 8	7 5	7 3	7 1	7 8	7 5	7 3	7 1	7 7	7 4	7 2	7 1	7 6	7 4	7 2	7 1	7 0
			0 . 5 6	1 . 0	8 0	7 8	7 6	7 4	8 0	7 7	7 5	7 4	7 9	7 6	7 5	7 3	7 8	7 6	7 4	7 3	7 2
			1 . 2 5	8 2	8 0	7 8	7 6	8 2	7 9	7 7	7 6	8 0	7 8	7 7	7 6	7 9	7 8	7 6	7 5	7 4	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 3	8 1	7 9	7 8	8 3	8 1	7 9	7 8	8 1	8 0	7 8	7 7	8 0	7 9	7 8	7 7	7 5	
			2 . 0	8 5	8 3	8 1	8 0	8 4	8 2	8 1	8 0	8 3	8 1	8 0	7 9	8 1	8 0	7 9	7 8	7 7	
			2 . 5	8 6	8 4	8 3	8 2	8 5	8 3	8 2	8 1	8 3	8 2	8 1	8 0	8 2	8 1	8 0	7 9	7 8	
取付 高さ	器具間隔最大限		3 . 0	8 6	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 2	8 2	8 1	8 0	7 9	
	横方向 (A)	縦方向 (B)	4 . 0	8 7	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 4	8 4	8 3	8 2	8 3	8 2	8 2	8 1	7 9	
H m	0 . 3 5 H m	0 . 3 5 H m	5 . 0	8 7	8 6	8 6	8 5	8 6	8 6	8 5	8 4	8 5	8 4	8 4	8 3	8 3	8 3	8 2	8 2	8 0	
			7 . 0	8 8	8 7	8 7	8 6	8 7	8 6	8 6	8 5	8 5	8 5	8 4	8 4	8 4	8 3	8 3	8 2	8 0	
			1 0 . 0	8 8	8 8	8 7	8 7	8 7	8 7	8 6	8 6	8 5	8 5	8 5	8 5	8 4	8 4	8 3	8 3	8 1	

