

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 3
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 6 5 3 (0) D R 1
B Z 分類	B Z 1

器具効率		27 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	25	24	23	23	25	24	23	23	24	24	23	23	24	24	23	23	22	
			0 . 6 3	0 . 8	26	25	24	24	26	25	24	24	25	25	24	24	25	24	24	24	23	
			0 . 5 6	1 . 0	26	26	25	25	26	25	25	24	26	25	25	24	25	25	25	24	24	
				1 . 2 5	27	26	26	25	27	26	25	25	26	26	25	25	26	25	25	25	24	
下方投影面積		c m ²	1 . 5	27	26	26	26	27	26	26	25	26	26	26	25	26	26	25	25	25		
			2 . 0	27	27	26	26	27	27	26	26	27	26	26	26	26	26	26	26	25		
等価発光面積		c m ²	2 . 5	28	27	27	27	27	27	27	26	27	27	26	26	26	26	26	26	25		
			3 . 0	28	27	27	27	28	27	27	27	27	27	27	26	27	26	26	26	25		
H m	0 . 7 7 H m	0 . 7 7 H m	4 . 0	28	28	27	27	28	27	27	27	27	27	27	27	27	27	26	26	26		
			5 . 0	28	28	28	27	28	28	27	27	27	27	27	27	27	27	27	26	26		
			7 . 0	28	28	28	28	28	28	28	27	27	27	27	27	27	27	27	27	26		
			1 0 . 0	28	28	28	28	28	28	28	28	27	27	27	27	27	27	27	27	26		

