

屋内照明器具特性

品番 (品名)	L G W 8 5 2 1 0 Z															
光源	LDA4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 1 m															
管理番号	K 0 1 4 0 5 7 4 (0) D B 1															
B Z 分類	B Z 1 0															

器具効率	87 %	天井	80 %					70 %					50 %					30 %					0 %					
	上方光束		76 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
	下方光束		11 %		床	10 %					10 %					10 %					10 %					0 %		
室指数	照明率 (X 0 . 0 1) Z C M																											
保守率	良	0.63	0.6	0.6	0.56	0.6	37	27	21	17	32	24	19	15	23	17	13	11	14	11	8	6	0					
	中	0.6	0.6	0.6	0.6	0.8	44	34	28	23	38	30	24	20	27	21	17	14	17	13	11	9	0					
	否	0.56	0.56	0.56	0.56	1.0	49	39	33	28	42	34	29	25	30	24	21	18	18	15	13	11	0					
下方投影面積 等価発光面積	c m ²	1.25	1.5	2.0	2.5	53	44	38	33	46	39	33	29	32	28	24	21	20	17	15	13	1						
		1.5	2.0	2.5	3.0	56	48	42	37	49	42	37	33	35	30	27	24	22	19	17	15	1						
		2.0	2.5	3.0	4.0	61	54	48	44	53	47	42	38	38	34	30	28	24	21	19	17	2						
取付高さ	器具間隔最大限		H m	0.00 H m	0.00 H m	2.5	3.0	4.0	5.0	7.0	10.0	63	57	53	48	55	50	46	42	40	36	33	31	25	23	21	19	2
	横方向 (A)	縦方向 (B)				3.0	4.0	5.0	7.0	10.0	65	60	56	52	57	53	49	45	41	38	35	33	26	24	22	21	3	
						4.0	5.0	7.0	10.0	68	64	60	56	59	56	52	50	43	40	38	36	27	26	24	23	4		
						5.0	7.0	10.0	70	66	63	60	61	58	55	52	44	42	40	38	28	27	26	24	4			
						7.0	10.0	72	69	66	64	63	60	58	56	46	44	42	41	30	29	27	26	5				
						10.0	73	71	69	67	64	63	61	59	47	46	45	43	31	30	29	28	6					

