

屋内照明器具特性	
品番 (品名)	LGW51705B
光源	LLD6300V ×1 1270.0 lm
管理番号	K0165623(0)DB1
BZ分類	BZ5

器具効率	68%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	66%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.8	2.9	2.4	2.0	3.7	2.9	2.4	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	2.0	1.8
	中	0.6	0.8	4.4	3.6	3.1	2.7	4.3	3.6	3.0	2.7	4.1	3.4	3.0	2.6	3.9	3.3	2.9	2.6	2.4
	否	0.56	1.0	4.9	4.1	3.6	3.2	4.7	4.0	3.5	3.2	4.5	3.9	3.5	3.1	4.3	3.8	3.4	3.1	2.9
			1.25	5.3	4.6	4.1	3.7	5.1	4.5	4.0	3.6	4.9	4.3	3.9	3.6	4.7	4.2	3.8	3.5	3.3
下方投影面積		cm ²	1.5	5.5	4.9	4.4	4.0	5.4	4.8	4.4	4.0	5.2	4.7	4.3	3.9	4.9	4.5	4.2	3.9	3.7
等価発光面積		cm ²	2.0	5.9	5.4	5.0	4.6	5.8	5.3	4.9	4.5	5.5	5.1	4.8	4.5	5.3	4.9	4.6	4.4	4.2
取付高さ	器具間隔最大限		2.5	6.2	5.7	5.3	5.0	6.0	5.6	5.2	4.9	5.8	5.4	5.1	4.8	5.5	5.2	5.0	4.7	4.5
	横方向 (A)	縦方向 (B)	3.0	6.3	5.9	5.6	5.3	6.2	5.8	5.5	5.2	5.9	5.6	5.3	5.1	5.7	5.4	5.2	5.0	4.8
Hm	1.26Hm	1.26Hm	4.0	6.6	6.2	5.9	5.7	6.4	6.1	5.8	5.6	6.2	5.9	5.7	5.5	5.9	5.7	5.5	5.3	5.1
			5.0	6.7	6.4	6.2	5.9	6.6	6.3	6.1	5.9	6.3	6.1	5.9	5.7	6.1	5.9	5.7	5.6	5.3
			7.0	6.8	6.6	6.4	6.3	6.7	6.5	6.3	6.2	6.5	6.3	6.2	6.0	6.3	6.1	6.0	5.9	5.6
			10.0	7.0	6.8	6.7	6.5	6.9	6.7	6.6	6.4	6.6	6.5	6.4	6.3	6.4	6.3	6.2	6.1	5.8

