

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | LGB16707                 |
| 光源       | LLD4000MLCE1 ×1 845.0 lm |
| 管理番号     | K0175676 (1) DR1         |
| BZ分類     | BZ2                      |

| 器具効率     |                          | 62 %<br><br>上方光束<br>2 %<br>下方光束<br>60 % | 反射率    | 天井   | 80 %            |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|--------------------------|-----------------------------------------|--------|------|-----------------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                          |                                         |        | 壁    | 70              | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                          |                                         |        | 床    | 10 %            |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                          |                                         |        | 室指数  | 照明率 ( X0.01 )   |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    | ZCM |
| 保守率      |                          | 良<br>中<br>否                             | 0.67   | 0.6  | 43              | 37  | 34 | 31 | 42   | 37 | 33 | 31 | 41   | 36 | 33 | 31 | 40   | 36 | 33 | 31 | 30  |
|          |                          |                                         | 0.63   | 0.8  | 48              | 43  | 39 | 37 | 47   | 42 | 39 | 37 | 46   | 42 | 39 | 36 | 44   | 41 | 38 | 36 | 35  |
|          |                          |                                         | 1.0    | 51   | 47              | 43  | 41 | 50 | 46   | 43 | 41 | 49 | 45   | 42 | 40 | 47 | 44   | 42 | 40 | 39 |     |
|          |                          |                                         | 0.56   | 1.25 | 54              | 50  | 47 | 44 | 53   | 49 | 46 | 44 | 52   | 48 | 46 | 44 | 50   | 47 | 45 | 43 | 42  |
| 下方投影面積   |                          | cm <sup>2</sup>                         | 1.5    | 56   | 52              | 49  | 47 | 55 | 52   | 49 | 47 | 53 | 50   | 48 | 46 | 52 | 49   | 47 | 46 | 44 |     |
|          |                          |                                         | 等価発光面積 |      | cm <sup>2</sup> | 2.0 | 58 | 55 | 53   | 51 | 57 | 55 | 52   | 50 | 56 | 53 | 51   | 50 | 54 | 52 | 50  |
| 取付<br>高さ | 器具間隔最大限                  |                                         | 2.5    | 60   |                 | 57  | 55 | 53 | 59   | 57 | 55 | 53 | 57   | 55 | 54 | 52 | 56   | 54 | 52 | 51 | 50  |
|          | 横方向 ( A )      縦方向 ( B ) |                                         | 3.0    | 61   | 59              | 57  | 55 | 60 | 58   | 56 | 55 | 58 | 57   | 55 | 54 | 57 | 55   | 54 | 53 | 51 |     |
| H m      | 1.23 H m      1.23 H m   |                                         | 4.0    | 62   | 60              | 59  | 58 | 61 | 60   | 58 | 57 | 60 | 58   | 57 | 56 | 58 | 57   | 56 | 55 | 53 |     |
|          |                          |                                         | 5.0    | 63   | 62              | 60  | 59 | 62 | 61   | 60 | 58 | 60 | 59   | 58 | 57 | 59 | 58   | 57 | 56 | 54 |     |
|          |                          |                                         | 7.0    | 64   | 63              | 62  | 61 | 63 | 62   | 61 | 60 | 61 | 60   | 60 | 59 | 60 | 59   | 58 | 58 | 56 |     |
|          |                          |                                         | 10.0   | 65   | 64              | 63  | 62 | 64 | 63   | 62 | 62 | 62 | 61   | 61 | 60 | 60 | 60   | 59 | 59 | 57 |     |

