

屋内照明器具特性

品番 (品名)	LGWC85044BZ				
光源	LDA4L-H-E17/E/S/W/2 x1		440.0 1 m		
管理番号	K0125233 (1) DB 1				
BZ分類	BZ4/0.7/BZ5				

器具効率	77%	天井 80%	70%				50%				30%				0%						
	上方光束 9%		70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束 68%		10%				10%				10%				10%				0%		
		室指数	照明率 (X0.01)																		ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	45	36	30	26	43	35	30	26	41	34	29	25	38	32	28	25	23		
		0.8	51	42	36	32	49	41	36	31	46	39	34	31	43	37	33	30	27		
		1.0	55	47	41	36	53	46	40	36	50	43	39	35	47	41	37	34	31		
		1.25	59	52	46	41	57	50	45	41	54	48	43	39	50	45	41	38	35		
下方投影面積 等価発光面積	cm ²		1.5	62	55	50	45	60	54	49	45	56	51	47	43	53	48	45	42	38	
	cm ²		2.0	66	60	55	51	64	59	54	50	60	56	52	48	57	53	50	47	43	
取付 高さ H _m	器具間隔最大限		2.5	69	64	59	55	67	62	58	54	63	59	55	52	59	56	53	50	46	
	横方向 (A)	縦方向 (B)	3.0	71	66	62	58	69	64	61	57	65	61	58	55	61	58	55	53	49	
	1.14H _m	1.16H _m	4.0	73	69	66	63	71	68	64	62	67	64	61	59	63	61	59	57	53	
			5.0	75	71	68	66	73	70	67	64	69	66	64	62	65	63	61	59	55	
			7.0	76	74	72	69	74	72	70	68	70	69	67	65	67	65	64	62	58	
			10.0	78	76	74	73	76	74	73	71	72	71	69	68	68	67	66	65	60	

