

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 7
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 4 7 0 (0) D R 1
B Z 分類	B Z 1 / 1 . 1 / B Z 2

器具効率		5 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		5 4 %																				
保守率		良 中 否	0 . 6 7	0 . 6	3 9	3 4	3 1	2 9	3 8	3 4	3 1	2 9	3 7	3 3	3 1	2 9	3 6	3 3	3 0	2 9	2 8	
			0 . 6 3	0 . 8	4 4	3 9	3 6	3 4	4 3	3 9	3 6	3 4	4 2	3 8	3 6	3 4	4 1	3 7	3 5	3 4	3 3	
			0 . 5 6	1 . 0	4 7	4 3	4 0	3 8	4 6	4 2	3 9	3 7	4 4	4 1	3 9	3 7	4 3	4 0	3 8	3 7	3 6	
				1 . 2 5	4 9	4 5	4 3	4 1	4 8	4 5	4 2	4 1	4 7	4 4	4 2	4 0	4 5	4 3	4 1	4 0	3 9	
下方投影面積		c m ²	1 . 5	5 1	4 7	4 5	4 3	5 0	4 7	4 5	4 3	4 8	4 6	4 4	4 2	4 7	4 5	4 3	4 2	4 1		
等価発光面積		c m ²	2 . 0	5 3	5 0	4 8	4 6	5 2	4 9	4 8	4 6	5 0	4 8	4 7	4 5	4 9	4 7	4 6	4 5	4 3		
取付 高さ	器具間隔最大限		2 . 5	5 4	5 2	5 0	4 8	5 3	5 1	4 9	4 8	5 2	5 0	4 8	4 7	5 0	4 9	4 8	4 6	4 5		
	横方向 (A)		縦方向 (B)	3 . 0	5 5	5 3	5 1	5 0	5 4	5 2	5 1	4 9	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 8	4 6	
H m	1 . 2 6 H m	1 . 2 6 H m	4 . 0	5 6	5 4	5 3	5 2	5 5	5 4	5 3	5 1	5 4	5 2	5 1	5 0	5 2	5 1	5 0	5 0	4 8		
			5 . 0	5 7	5 5	5 4	5 3	5 6	5 5	5 4	5 3	5 4	5 3	5 2	5 2	5 3	5 2	5 1	5 1	4 9		
			7 . 0	5 7	5 6	5 6	5 5	5 6	5 6	5 5	5 4	5 5	5 4	5 4	5 3	5 3	5 3	5 2	5 2	5 0		
			1 0 . 0	5 8	5 7	5 7	5 6	5 7	5 6	5 6	5 5	5 6	5 5	5 5	5 4	5 4	5 4	5 3	5 3	5 1		

