

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 7
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190472 (0) DR 1
B Z 分類	BZ1 / 0.9 / BZ2

器具効率		55 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	39	34	31	29	38	34	31	29	37	33	30	28	36	32	30	28	27
			0.63	0.8	43	39	36	34	42	38	36	33	41	38	35	33	40	37	35	33	32
			0.56	1.0	46	42	39	37	45	42	39	37	44	41	38	37	43	40	38	36	35
				1.25	48	45	42	40	48	44	42	40	46	43	41	40	45	42	41	39	38
下方投影面積		cm ²		1.5	50	47	44	42	49	46	44	42	48	45	43	42	46	44	43	41	40
				2.0	52	49	47	46	51	49	47	45	50	48	46	45	48	47	45	44	43
等価発光面積		cm ²		2.5	53	51	49	48	53	50	49	47	51	49	48	47	49	48	47	46	44
				3.0	54	52	51	49	53	52	50	49	52	50	49	48	50	49	48	47	45
H m	1.26 H m		1.26 H m	4.0	55	54	52	51	54	53	52	51	53	52	51	50	51	50	50	49	47
				5.0	56	55	54	53	55	54	53	52	54	53	52	51	52	51	51	50	48
				7.0	57	56	55	54	56	55	54	54	54	54	53	52	53	52	52	51	49
				10.0	57	57	56	55	56	56	55	55	55	54	54	53	53	53	53	52	50

