

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 8
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 7 7 2 (0) D R 1
B Z 分類	B Z 1 / 0 . 9 / B Z 2

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		2 % 61 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.67	0.6	45	39	36	33	44	39	35	33	43	38	35	33	41	37	35	33	32	
			0.63	0.8	50	45	41	39	49	44	41	39	48	44	41	38	46	43	40	38	37	
			1.0	1.0	53	49	45	43	52	48	45	43	51	47	44	42	49	46	44	42	41	
			0.56	1.25	56	52	49	47	55	51	48	46	53	50	48	46	52	49	47	45	44	
下方投影面積 等価発光面積		cm ² cm ²	1.5	1.5	58	54	51	49	57	54	51	49	55	52	50	48	53	51	49	48	46	
			2.0	2.0	60	57	55	53	59	57	54	52	57	55	53	52	56	54	52	51	49	
取付 高さ	器具間隔最大限		2.5	2.5	62	59	57	55	61	58	56	55	59	57	55	54	57	56	54	53	51	
	横方向 (A) 縦方向 (B)		3.0	3.0	63	60	59	57	62	60	58	56	60	58	57	55	58	57	56	54	53	
H m	1.26 H m	1.26 H m	4.0	4.0	64	62	61	59	63	61	60	59	61	60	59	58	59	58	57	56	54	
			5.0	5.0	65	63	62	61	64	62	61	60	62	61	60	59	60	59	58	58	56	
			7.0	7.0	66	65	64	63	65	64	63	62	63	62	61	61	61	60	60	59	57	
			10.0	10.0	66	65	65	64	65	65	64	63	63	63	62	62	62	61	61	60	58	

