

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 8
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0175770 (0) DR 1
B Z 分類	BZ1 / 1.1 / BZ2

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	45	39	36	33	44	39	35	33	43	38	35	33	42	38	35	33	32
			0.63	0.8	50	45	41	39	49	44	41	39	48	44	41	39	46	43	40	38	37
			0.56	1.0	53	49	45	43	52	48	45	43	51	47	44	42	49	46	44	42	41
				1.25	56	52	49	47	55	51	49	46	53	50	48	46	52	49	47	45	44
下方投影面積 等価発光面積		c m ² c m ²		1.5	58	54	51	49	57	54	51	49	55	52	50	48	54	51	49	48	46
				2.0	60	57	55	53	59	56	54	52	57	55	53	52	56	54	52	51	49
				2.5	62	59	57	55	61	58	56	55	59	57	55	54	57	56	54	53	51
				3.0	63	60	59	57	62	60	58	56	60	58	57	56	58	57	56	55	53
H m	1.26 H m	1.26 H m		4.0	64	62	61	59	63	61	60	59	61	60	59	58	59	58	57	57	55
				5.0	65	63	62	61	64	62	61	60	62	61	60	59	60	59	59	58	56
				7.0	65	64	63	63	64	64	63	62	63	62	61	61	61	60	60	59	57
				10.0	66	65	65	64	65	64	64	63	63	63	62	62	62	61	61	60	58

