

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 8
光源	LLD5000LCC1 ×1 1140.0 l m
管理番号	K0190390 (0) DR 1
B Z 分類	BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 75 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	54	48	44	41	54	48	44	41	52	47	44	41	51	47	43	41	40	
			0.63	0.8	61	55	51	48	60	55	51	48	58	54	51	48	57	53	50	48	47	
			1.0	65	60	56	53	64	59	56	53	62	58	55	53	61	57	55	53	51		
			0.56	1.25	68	63	60	57	67	63	60	57	65	62	59	57	64	61	58	56	55	
下方投影面積		cm ²	1.5	70	66	63	60	69	65	62	60	67	64	62	60	66	63	61	59	58		
等価発光面積			2.0	73	69	67	64	72	69	66	64	70	67	65	64	68	66	64	63	61		
取付 高さ	器具間隔最大限		2.5	74	71	69	67	73	71	69	67	72	69	68	66	70	68	67	65	64		
	横方向 (A) 縦方向 (B)		3.0	75	73	71	69	74	72	70	69	73	71	69	68	71	70	68	67	65		
H m	1.29 H m	1.29 H m	4.0	77	75	73	72	76	74	73	71	74	73	71	70	72	71	70	69	67		
			5.0	77	76	75	73	77	75	74	73	75	74	73	72	73	72	71	71	69		
			7.0	78	77	76	75	77	76	75	75	76	75	74	73	74	73	73	72	70		
			10.0	79	78	77	77	78	77	77	76	76	76	75	75	75	74	74	73	71		

