

屋内照明器具特性

品番 (品名)	L G W J 8 5 1 1 5 U														
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m														
管理番号	K0125722 (1) DB 1														
B Z 分類	B Z 5														

器具効率	42 %	天井	80 %				70 %				50 %				30 %				0 %		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
		床	10 %				10 %				10 %				10 %				0 %		
上方光束	5 %	室指数																			
下方光束	37 %	照明率 (X0.01)																			
		Z C M																			
保守率	良 中 否	0.63	0.6	23	17	14	12	22	17	14	11	20	16	13	11	19	15	13	11	10	
		0.6	0.8	27	22	18	16	26	21	18	15	24	20	17	15	22	19	16	14	13	
		0.56	1.0	29	25	21	19	28	24	21	18	26	23	20	18	24	21	19	17	16	
			1.25	32	27	24	22	31	27	24	21	28	25	23	21	27	24	22	20	18	
下方投影面積		c m ²		1.5	33	30	26	24	32	29	26	24	30	27	25	23	28	26	24	22	20
等価発光面積		c m ²		2.0	36	33	30	28	35	32	29	27	32	30	28	26	30	28	26	25	23
取付高さ	器具間隔最大限		2.5	37	34	32	30	36	34	31	29	34	32	30	28	32	30	28	27	25	
	横方向 (A)	縦方向 (B)	3.0	38	36	34	32	37	35	33	31	35	33	31	30	33	31	30	28	26	
H m	1.24 H m	1.30 H m	4.0	40	38	36	34	39	37	35	34	36	35	33	32	34	33	32	31	28	
			5.0	41	39	37	36	39	38	36	35	37	36	35	34	35	34	33	32	30	
			7.0	42	40	39	38	40	39	38	37	38	37	36	35	36	35	34	34	31	
			10.0	42	41	41	40	41	40	40	39	39	38	38	37	37	36	36	35	32	

