

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 7 8
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184642 (0) DR 1
B Z 分類	BZ1 / 0.9 / BZ2

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		3 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		55 %																						
保守率		良 中 否	0.67	0.6	41	36	32	30	40	35	32	30	39	35	32	30	38	34	31	30	29			
			0.63	0.8	46	41	38	36	45	41	38	35	43	40	37	35	42	39	36	35	33			
			0.56	1.0	49	44	41	39	48	44	41	39	46	43	40	38	45	42	40	38	37			
				1.25	51	48	45	43	50	47	44	42	49	46	43	42	47	45	43	41	40			
下方投影面積		c m ²	1.5	53	50	47	45	52	49	46	45	50	48	46	44	49	46	45	43	42				
等価発光面積			c m ²	2.0	55	52	50	48	54	52	50	48	52	50	48	47	51	49	47	46	44			
取付 高さ	器具間隔最大限		2.5	57	54	52	51	56	53	52	50	54	52	50	49	52	50	49	48	46				
	横方向 (A)		縦方向 (B)		3.0	57	55	54	52	56	55	53	52	55	53	52	50	53	52	50	49	47		
H m	1.23 H m		1.23 H m		4.0	59	57	56	54	58	56	55	54	56	55	53	52	54	53	52	51	49		
					5.0	59	58	57	56	58	57	56	55	56	55	54	54	55	54	53	52	50		
					7.0	60	59	58	57	59	58	57	57	57	56	56	55	55	55	54	54	51		
					10.0	61	60	59	59	60	59	58	58	58	57	57	56	56	55	55	55	52		

