

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 7 8
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 1 m
管理番号	K 0 1 8 4 6 4 3 (0) D R 1
B Z 分類	B Z 1

器具効率		8 5 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 4 %																					
保守率		良	0 . 6 7	0 . 6	7 5	7 1	6 9	6 7	7 5	7 1	6 9	6 7	7 4	7 0	6 8	6 7	7 3	7 0	6 8	6 6	6 6		
		中	0 . 6 3	0 . 8	7 9	7 5	7 3	7 1	7 8	7 5	7 3	7 1	7 7	7 4	7 2	7 1	7 6	7 4	7 2	7 0	6 9		
		否	0 . 5 6	1 . 0	8 1	7 8	7 6	7 4	8 1	7 8	7 5	7 4	7 9	7 7	7 5	7 3	7 8	7 6	7 4	7 3	7 2		
				1 . 2 5	8 3	8 0	7 8	7 6	8 3	8 0	7 8	7 6	8 1	7 9	7 7	7 6	8 0	7 8	7 6	7 5	7 4		
下方投影面積		c m ²		1 . 5	8 5	8 2	8 0	7 8	8 4	8 1	7 9	7 8	8 2	8 0	7 9	7 7	8 1	7 9	7 8	7 7	7 5		
等価発光面積		c m ²		2 . 0	8 6	8 4	8 2	8 1	8 5	8 3	8 2	8 0	8 4	8 2	8 1	7 9	8 2	8 1	8 0	7 9	7 7		
取付 高さ	器具間隔最大限			2 . 5	8 7	8 5	8 4	8 2	8 6	8 5	8 3	8 2	8 5	8 3	8 2	8 1	8 3	8 2	8 1	8 0	7 8		
	横方向 (A)		縦方向 (B)	3 . 0	8 8	8 6	8 5	8 4	8 7	8 6	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 3	8 2	8 1	7 9		
H m	0 . 7 8 H m	0 . 7 8 H m	4 . 0	8 9	8 7	8 6	8 5	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 3	8 4	8 3	8 3	8 2	8 0			
			5 . 0	8 9	8 8	8 7	8 6	8 8	8 7	8 6	8 6	8 6	8 6	8 5	8 4	8 5	8 4	8 3	8 3	8 1			
			7 . 0	9 0	8 9	8 8	8 8	8 9	8 8	8 8	8 7	8 7	8 6	8 6	8 5	8 5	8 5	8 4	8 4	8 1			
			1 0 . 0	9 0	9 0	8 9	8 9	8 9	8 9	8 8	8 8	8 7	8 7	8 7	8 6	8 5	8 5	8 5	8 4	8 2			

