

屋内照明器具特性	
品番 (品名)	LGB10830
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184496 (0) DR 1
BZ分類	BZ1

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		1 %	室指数	照明率 (X0.01)																				ZCM	
下方光束		88 %																							
保守率		良 中 否	0.67	0.6	67	61	56	53	67	60	56	53	65	59	56	53	64	59	55	53	51				
			0.63	0.8	74	68	64	61	73	67	64	61	71	67	63	60	70	66	62	60	59				
			0.56	1.0	78	73	69	66	77	72	68	66	75	71	68	65	74	70	67	65	63				
				1.25	82	77	73	70	81	76	73	70	79	75	72	69	77	74	71	69	67				
下方投影面積		c m ²		1.5	84	80	76	74	83	79	76	73	81	77	75	72	79	76	74	72	70				
等価発光面積			c m ²	2.0	87	83	80	78	86	83	80	78	84	81	79	77	82	79	77	76	74				
取付 高さ	器具間隔最大限		2.5	89	86	83	81	88	85	82	80	85	83	81	79	83	81	80	78	76					
	横方向 (A)		縦方向 (B)	3.0	90	87	85	83	89	86	84	82	86	84	83	81	84	83	81	80	78				
H m	0.72 H m	0.72 H m	4.0	91	89	87	86	90	88	86	85	88	86	85	84	86	85	83	82	80					
			5.0	92	90	89	87	91	89	88	87	89	87	86	85	87	86	85	84	81					
			7.0	93	92	91	90	92	91	90	89	90	89	88	87	88	87	86	85	83					
			10.0	94	93	92	91	93	92	91	90	90	90	89	88	88	88	87	87	84					

