

屋内照明器具特性	
品番 (品名)	LGB15452
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0170957(0)DR1
BZ分類	BZ6/0.7/BZ5/1.1/BZ6

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束		26%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	72%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	50	39	31	26	48	37	30	25	43	34	28	23	39	31	26	22	18
	中	0.63	0.8	59	48	40	34	56	46	39	33	50	42	36	31	45	38	33	29	25
	否	0.56	1.0	65	54	46	41	62	52	45	39	55	47	41	37	50	43	38	34	29
			1.25	71	60	53	47	67	58	51	45	60	53	47	42	54	48	43	39	33
下方投影面積	c m <sup>2</sup>		1.5	74	65	58	52	71	62	55	50	63	57	51	47	57	51	47	43	37
	等価発光面積		c m <sup>2</sup>	2.0	80	71	65	59	76	68	62	57	68	62	57	53	61	57	53	49
取付高さ	器具間隔最大限		2.5	83	76	70	65	79	72	67	62	71	66	62	58	64	60	56	53	46
	横方向 (A)	縦方向 (B)	3.0	85	79	73	69	81	76	71	66	74	69	65	61	66	63	59	56	48
H m	1.34 H m	1.34 H m	4.0	88	83	79	74	84	80	75	72	77	73	69	66	69	66	63	61	52
			5.0	90	86	82	78	86	82	79	75	79	75	72	69	71	69	66	64	55
			7.0	93	89	86	83	89	86	83	80	81	78	76	74	74	72	70	68	59
			10.0	95	92	90	87	91	88	86	84	83	81	79	77	76	74	73	71	62

