

屋内照明器具特性

品番 (品名)	NNF 2 6 9 0 9 J	
光源	LED5000_70_3655 x1	3655.0 lm
管理番号	K0129512 (0) DB 1	
BZ分類	BZ6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		14 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		86 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.69	0.6	5.2	3.9	3.1	2.6	5.0	3.8	3.0	2.5	4.6	3.6	2.9	2.4	4.3	3.4	2.8	2.3	2.0	
	中	0.67	0.8	6.1	4.9	4.1	3.5	5.9	4.8	4.0	3.4	5.4	4.5	3.8	3.3	5.0	4.2	3.6	3.2	2.8	
	否	0.63	1.0	6.8	5.6	4.8	4.1	6.5	5.4	4.6	4.1	6.0	5.1	4.4	3.9	5.6	4.8	4.2	3.8	3.4	
			1.25	7.3	6.3	5.5	4.8	7.1	6.1	5.3	4.7	6.5	5.7	5.1	4.5	6.1	5.4	4.8	4.4	3.9	
下方投影面積 等価発光面積	c m ²		1.5	7.7	6.8	6.0	5.4	7.5	6.5	5.8	5.3	6.9	6.2	5.5	5.0	6.4	5.8	5.3	4.8	4.4	
	c m ²		2.0	8.3	7.5	6.8	6.2	8.0	7.2	6.6	6.1	7.5	6.8	6.3	5.8	6.9	6.4	5.9	5.5	5.0	
	c m ²		2.5	8.7	7.9	7.3	6.8	8.4	7.7	7.1	6.6	7.8	7.2	6.8	6.3	7.3	6.8	6.4	6.0	5.5	
取付高さ	器具間隔最大限		3.0	8.9	8.3	7.7	7.2	8.6	8.0	7.5	7.0	8.1	7.6	7.1	6.7	7.5	7.1	6.8	6.4	5.9	
	横方向 (A)	縦方向 (B)																			
1.5m	2.08 m	2.05 m	4.0	9.3	8.7	8.3	7.8	9.0	8.5	8.0	7.6	8.4	8.0	7.6	7.3	7.9	7.5	7.2	7.0	6.4	
2	2.76	2.65	5.0	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.0	8.6	8.3	8.0	7.7	8.1	7.8	7.6	7.3	6.7	
2.5	3.44	3.27	7.0	9.8	9.4	9.1	8.7	9.5	9.1	8.8	8.5	8.9	8.6	8.4	8.1	8.4	8.2	7.9	7.7	7.1	
3	4.12	3.89	10.0	10.0	9.7	9.4	9.2	9.7	9.4	9.2	9.0	9.1	8.9	8.7	8.5	8.6	8.4	8.3	8.1	7.5	

