

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | NNF 2 6 9 0 8 J     |           |
| 光源      | LED4000_70_3530 x1  | 3530.0 lm |
| 管理番号    | K0129512 ( 0 ) DB 1 |           |
| BZ分類    | BZ6                 |           |

|                  |                  |        |           |      |     |      |      |     |     |      |      |     |     |      |      |     |     |      |     |     |     |
|------------------|------------------|--------|-----------|------|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|-----|-----|-----|
| 器具効率             | 100 %            | 天井     | 80 %      |      |     |      | 70 % |     |     |      | 50 % |     |     |      | 30 % |     |     |      | 0 % |     |     |
|                  | 上方光束             |        | 14 %      | 反射率  | 70  | 50   | 30   | 10  | 70  | 50   | 30   | 10  | 70  | 50   | 30   | 10  | 70  | 50   | 30  | 10  | 0 % |
|                  | 下方光束             |        | 86 %      |      | 床   | 10 % |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 10 % |     |     |     |
| 室指数              | 照明率 ( X0.01 )    |        |           |      |     |      |      |     |     |      |      |     |     |      |      |     |     |      |     |     | ZCM |
| 保守率              | 良                | 0.69   | 0.6       | 5.2  | 3.9 | 3.1  | 2.6  | 5.0 | 3.8 | 3.0  | 2.5  | 4.6 | 3.6 | 2.9  | 2.4  | 4.3 | 3.4 | 2.8  | 2.3 | 2.0 |     |
|                  | 中                | 0.67   | 0.8       | 6.1  | 4.9 | 4.1  | 3.5  | 5.9 | 4.8 | 4.0  | 3.4  | 5.4 | 4.5 | 3.8  | 3.3  | 5.0 | 4.2 | 3.6  | 3.2 | 2.8 |     |
|                  | 否                | 0.63   | 1.0       | 6.8  | 5.6 | 4.8  | 4.1  | 6.5 | 5.4 | 4.6  | 4.1  | 6.0 | 5.1 | 4.4  | 3.9  | 5.6 | 4.8 | 4.2  | 3.8 | 3.4 |     |
|                  |                  |        | 1.25      | 7.3  | 6.3 | 5.5  | 4.8  | 7.1 | 6.1 | 5.3  | 4.7  | 6.5 | 5.7 | 5.1  | 4.5  | 6.1 | 5.4 | 4.8  | 4.4 | 3.9 |     |
| 下方投影面積<br>等価発光面積 | c m <sup>2</sup> |        | 1.5       | 7.7  | 6.8 | 6.0  | 5.4  | 7.5 | 6.5 | 5.8  | 5.3  | 6.9 | 6.2 | 5.5  | 5.0  | 6.4 | 5.8 | 5.3  | 4.8 | 4.4 |     |
|                  | c m <sup>2</sup> |        | 2.0       | 8.3  | 7.5 | 6.8  | 6.2  | 8.0 | 7.2 | 6.6  | 6.1  | 7.5 | 6.8 | 6.3  | 5.8  | 6.9 | 6.4 | 5.9  | 5.5 | 5.0 |     |
|                  | 器具間隔最大限          |        | 2.5       | 8.7  | 7.9 | 7.3  | 6.8  | 8.4 | 7.7 | 7.1  | 6.6  | 7.8 | 7.2 | 6.8  | 6.3  | 7.3 | 6.8 | 6.4  | 6.0 | 5.5 |     |
| 取付高さ             | 横方向 ( A )        |        | 縦方向 ( B ) |      | 3.0 | 8.9  | 8.3  | 7.7 | 7.2 | 8.6  | 8.0  | 7.5 | 7.0 | 8.1  | 7.6  | 7.1 | 6.7 | 7.5  | 7.1 | 6.8 | 6.4 |
|                  | 1.5m             | 2.08 m | 2.05 m    | 4.0  | 9.3 | 8.7  | 8.3  | 7.8 | 9.0 | 8.5  | 8.0  | 7.6 | 8.4 | 8.0  | 7.6  | 7.3 | 7.9 | 7.5  | 7.2 | 7.0 |     |
| 2                | 2.76             | 2.65   | 5.0       | 9.5  | 9.0 | 8.6  | 8.2  | 9.2 | 8.8 | 8.4  | 8.0  | 8.6 | 8.3 | 8.0  | 7.7  | 8.1 | 7.8 | 7.6  | 7.3 |     |     |
| 2.5              | 3.44             | 3.27   | 7.0       | 9.8  | 9.4 | 9.1  | 8.7  | 9.5 | 9.1 | 8.8  | 8.5  | 8.9 | 8.6 | 8.4  | 8.1  | 8.4 | 8.2 | 7.9  | 7.7 |     |     |
| 3                | 4.12             | 3.89   | 10.0      | 10.0 | 9.7 | 9.4  | 9.2  | 9.7 | 9.4 | 9.2  | 9.0  | 9.1 | 8.9 | 8.7  | 8.5  | 8.6 | 8.4 | 8.3  | 8.1 |     |     |

