

屋内照明器具特性	
品番 (品名)	LGB16130
光源	LLD5020LCC1 ×1 1085.0 l m
管理番号	K0190436 (0) DR 1
B Z 分類	BZ1

器具効率		79 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %	室指数	床	10 %				10 %				10 %				10 %				0 %
下方光束		79 %		照明率 (X0.01)																Z C M	
保守率		良	0.6	67	62	59	57	66	62	59	57	65	61	59	57	64	61	58	57	56	
		中	0.8	72	68	65	63	71	67	65	63	70	67	64	63	69	66	64	62	61	
		否	1.0	74	71	68	67	74	71	68	66	73	70	68	66	71	69	67	66	65	
		0.56	1.25	77	74	72	70	76	73	71	70	75	73	71	69	74	72	70	69	68	
下方投影面積		c m ²	1.5	78	76	74	72	78	75	73	72	76	74	73	71	75	73	72	71	70	
等価発光面積			c m ²	2.0	80	78	77	75	80	78	76	75	78	77	75	74	77	76	75	74	72
取付 高さ	器具間隔最大限		2.5	82	80	79	77	81	79	78	77	79	78	77	76	78	77	76	75	74	
	横方向 (A)		縦方向 (B)	3.0	82	81	80	79	82	80	79	78	80	79	78	77	79	78	77	76	75
H m	0.41 H m	0.41 H m	4.0	83	82	81	81	82	82	81	80	81	80	80	79	80	79	78	78	76	
			5.0	84	83	82	82	83	82	82	81	81	81	81	80	80	80	79	79	77	
			7.0	85	84	84	83	84	83	83	83	82	82	82	81	81	80	80	80	78	
			10.0	85	85	85	84	84	84	84	84	83	82	82	82	81	81	81	81	79	

