

屋内照明器具特性

品番 (品名)	NNF 2 6 9 0 2 J	
光源	LED3500_70_2120 x1 2120.0 lm	
管理番号	K0129511 (0) DB 1	
BZ分類	BZ6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	14 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	86 %		室指数	照明率 (X0.01)																			
保守率	良 中 否	0.69	0.6	5.2	3.9	3.1	2.5	5.0	3.8	3.0	2.5	4.6	3.6	2.9	2.4	4.2	3.4	2.8	2.3	2.0			
		0.67	0.8	6.1	4.9	4.1	3.4	5.9	4.7	4.0	3.4	5.4	4.5	3.8	3.3	5.0	4.2	3.6	3.1	2.8			
			1.0	6.7	5.6	4.7	4.1	6.5	5.4	4.6	4.0	6.0	5.1	4.4	3.9	5.5	4.8	4.2	3.7	3.3			
		0.63	1.25	7.3	6.2	5.4	4.8	7.0	6.1	5.3	4.7	6.5	5.7	5.0	4.5	6.0	5.3	4.8	4.3	3.9			
下方投影面積	c m ²	1.5	7.7	6.7	6.0	5.3	7.4	6.5	5.8	5.2	6.9	6.1	5.5	5.0	6.4	5.8	5.2	4.8	4.3				
		2.0	8.3	7.4	6.7	6.2	8.0	7.2	6.6	6.0	7.4	6.8	6.2	5.8	6.9	6.4	5.9	5.5	5.0				
取付高さ	器具間隔最大限		2.5	8.7	7.9	7.3	6.7	8.4	7.7	7.1	6.6	7.8	7.2	6.7	6.3	7.3	6.8	6.4	6.0	5.5			
	横方向 (A)	縦方向 (B)	3.0	8.9	8.3	7.7	7.2	8.6	8.0	7.5	7.0	8.1	7.6	7.1	6.7	7.5	7.1	6.7	6.4	5.8			
1.5m	2.07 m	1.97 m	4.0	9.3	8.7	8.2	7.8	9.0	8.5	8.0	7.6	8.4	8.0	7.6	7.3	7.9	7.5	7.2	6.9	6.3			
2	2.75	2.59	5.0	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.0	8.6	8.3	7.9	7.6	8.1	7.8	7.5	7.3	6.7			
2.5	3.44	3.22	7.0	9.7	9.4	9.1	8.7	9.5	9.1	8.8	8.5	8.9	8.6	8.4	8.1	8.4	8.1	7.9	7.7	7.1			
3	4.12	3.84	10.0	10.0	9.7	9.4	9.2	9.7	9.4	9.2	9.0	9.1	8.9	8.7	8.5	8.6	8.4	8.3	8.1	7.4			

