

屋内照明器具特性		
品番 (品名)	L G B 1 0 8 3 2	
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 1 m	
管理番号	K 0 1 8 4 4 9 8 (0) D R 1	
B Z 分類	B Z 1	

器具効率		8 9 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		2 %	8 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																							
保守率		良 中 否	0 . 6	6 8	6 1	5 6	5 3	6 7	6 0	5 6	5 3	6 5	6 0	5 6	5 3	6 4	5 9	5 5	5 3	5 2			
			0 . 6 3	0 . 8	7 4	6 8	6 4	6 1	7 3	6 8	6 4	6 1	7 2	6 7	6 3	6 1	7 0	6 6	6 3	6 0	5 9		
			1 . 0	7 9	7 3	6 9	6 6	7 8	7 3	6 9	6 6	7 6	7 1	6 8	6 6	7 4	7 0	6 7	6 5	6 4			
			0 . 5 6	1 . 2 5	8 2	7 7	7 4	7 1	8 1	7 7	7 3	7 1	7 9	7 5	7 2	7 0	7 7	7 4	7 2	6 9	6 8		
下方投影面積		c m ²	1 . 5	8 4	8 0	7 7	7 4	8 3	7 9	7 6	7 4	8 1	7 8	7 5	7 3	7 9	7 7	7 4	7 2	7 1			
			2 . 0	8 7	8 4	8 1	7 9	8 6	8 3	8 0	7 8	8 4	8 1	7 9	7 7	8 2	8 0	7 8	7 6	7 4			
取付 高さ	器具間隔最大限		2 . 5	8 9	8 6	8 4	8 2	8 8	8 5	8 3	8 1	8 6	8 3	8 2	8 0	8 4	8 2	8 0	7 9	7 7			
	横方向 (A)	縦方向 (B)	3 . 0	9 0	8 8	8 5	8 4	8 9	8 7	8 5	8 3	8 7	8 5	8 3	8 2	8 5	8 3	8 2	8 0	7 8			
H m	0 . 7 5 H m	0 . 7 5 H m	4 . 0	9 1	9 0	8 8	8 6	9 0	8 9	8 7	8 5	8 8	8 7	8 5	8 4	8 6	8 5	8 4	8 3	8 0			
			5 . 0	9 2	9 1	8 9	8 8	9 1	9 0	8 8	8 7	8 9	8 8	8 7	8 6	8 7	8 6	8 5	8 4	8 2			
			7 . 0	9 3	9 2	9 1	9 0	9 2	9 1	9 0	8 9	9 0	8 9	8 8	8 7	8 8	8 7	8 6	8 6	8 3			
			1 0 . 0	9 4	9 3	9 2	9 2	9 3	9 2	9 1	9 1	9 1	9 0	8 9	8 9	8 8	8 8	8 7	8 7	8 4			

