

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 3 3
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176330 (0) DR 1
B Z 分類	BZ4 / 2.8 / BZ5

器具効率		73 % 上方光束 4 % 下方光束 69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	42	34	28	25	41	33	28	24	39	32	28	24	37	31	27	24	22
			0.63	0.8	50	42	36	32	48	41	36	32	46	40	35	32	44	38	34	31	29
			0.56	1.0	54	47	42	38	53	46	41	37	50	45	40	37	48	43	39	36	34
			1.25	59	52	47	43	57	51	46	42	54	49	45	42	52	47	44	41	39	
下方投影面積		c m ²	1.5	61	55	50	47	60	54	50	46	57	52	48	45	54	50	47	44	42	
等価発光面積			c m ²	2.0	65	60	56	52	64	59	55	52	61	57	53	50	58	55	52	49	47
取付	器具間隔最大限			2.5	68	63	59	56	66	62	58	55	63	60	57	54	60	58	55	53	50
高さ	横方向 (A)		縦方向 (B)	3.0	69	65	62	59	68	64	61	58	65	62	59	57	62	60	57	55	53
H m	1.30 H m		1.30 H m	4.0	71	68	65	63	70	67	64	62	67	65	62	60	64	62	60	59	56
				5.0	73	70	68	65	71	69	66	64	68	66	64	63	66	64	62	61	58
				7.0	74	72	70	69	73	71	69	68	70	68	67	66	67	66	65	64	61
				10.0	75	74	72	71	74	73	71	70	71	70	69	68	69	68	67	66	63

