

屋内照明器具特性	
品番 (品名)	LGB10833
光源	LLD3020CU1 ×1 615.0 lm
管理番号	K0179079 (0) DR1
BZ分類	BZ1

器具効率		85 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		85 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束																								
保守率		良 中 否	0.67	0.6	71	66	63	60	70	66	63	60	69	65	62	60	68	65	62	60	59			
			0.63	0.8	76	71	68	66	75	71	68	65	74	70	67	65	72	69	67	65	64			
			0.56	1.0	79	74	71	69	78	74	71	69	76	73	71	69	75	72	70	68	67			
				1.25	81	77	74	72	80	77	74	72	79	76	73	72	77	75	73	71	70			
下方投影面積		c m ²	1.5	83	79	77	75	82	79	76	74	80	78	75	74	79	76	75	73	72				
等価発光面積			c m ²	2.0	85	82	80	78	84	81	79	77	82	80	78	77	81	79	77	76	74			
取付 高さ	器具間隔最大限			2.5	86	84	82	80	85	83	81	79	83	82	80	79	82	80	79	78	76			
	横方向 (A)		縦方向 (B)		3.0	87	85	83	81	86	84	82	81	84	83	81	80	83	81	80	79	77		
H m	0.36 H m	0.36 H m	4.0	88	86	85	84	87	86	84	83	85	84	83	82	84	83	82	81	79				
			5.0	89	87	86	85	88	86	85	84	86	85	84	83	84	83	83	82	80				
			7.0	90	88	88	87	89	88	87	86	87	86	85	84	85	84	84	83	81				
			10.0	90	89	89	88	89	88	88	87	87	87	86	86	85	85	85	84	82				

