

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 3 3
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184499 (1) DR 1
B Z 分類	BZ4 / 2.8 / BZ5

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		4 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		69 %																						
保守率		良 中 否	0.67	0.6	43	34	29	25	42	34	28	25	39	32	28	24	37	31	27	24	22			
			0.63	0.8	50	42	36	32	48	41	36	32	46	40	35	32	44	38	34	31	29			
			1.0	54	47	42	37	53	46	41	37	50	44	40	37	48	43	39	36	34				
			0.56	1.25	58	52	47	43	57	51	46	42	54	49	45	41	52	47	44	41	38			
下方投影面積		c m ²	1.5	61	55	50	46	60	54	50	46	57	52	48	45	54	50	47	44	42				
等価発光面積			c m ²	2.0	65	60	56	52	63	59	55	51	61	57	53	50	58	54	52	49	47			
取付 高さ	器具間隔最大限		2.5	67	63	59	56	66	62	58	55	63	59	56	54	60	57	55	53	50				
	横方向 (A)		縦方向 (B)		3.0	69	65	62	59	67	64	61	58	65	62	59	57	62	59	57	55	52		
H m	1.25 H m	1.25 H m	4.0	71	68	65	63	70	67	64	62	67	64	62	60	64	62	60	59	56				
			5.0	72	70	67	65	71	69	66	64	68	66	64	63	65	64	62	61	58				
			7.0	74	72	70	68	73	71	69	67	70	68	67	65	67	66	65	64	60				
			10.0	75	74	72	71	74	72	71	70	71	70	69	68	68	67	67	66	62				

