

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 3 3
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 9 9 3 5 (1) D R 1
B Z 分類	B Z 4 / 2 . 8 / B Z 5

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	5 0	4 0	3 4	2 9	4 9	3 9	3 3	2 9	4 6	3 8	3 3	2 9	4 4	3 7	3 2	2 8	2 6	
			0 . 6 3	0 . 8	5 9	4 9	4 3	3 8	5 7	4 9	4 2	3 8	5 4	4 7	4 1	3 7	5 2	4 5	4 1	3 7	3 5	
			0 . 5 6	1 . 0	6 4	5 6	4 9	4 5	6 3	5 5	4 9	4 4	6 0	5 3	4 8	4 4	5 7	5 1	4 6	4 3	4 0	
				1 . 2 5	6 9	6 1	5 5	5 1	6 7	6 0	5 5	5 0	6 4	5 8	5 3	4 9	6 1	5 6	5 2	4 8	4 6	
下方投影面積		c m ²	1 . 5	7 3	6 5	6 0	5 5	7 1	6 4	5 9	5 5	6 7	6 2	5 7	5 3	6 4	6 0	5 6	5 2	5 0		
等価発光面積			2 . 0	7 7	7 1	6 6	6 2	7 5	7 0	6 5	6 1	7 2	6 7	6 3	6 0	6 9	6 5	6 1	5 8	5 5		
取付 高さ	器具間隔最大限		2 . 5	8 0	7 5	7 0	6 6	7 8	7 3	6 9	6 5	7 5	7 0	6 7	6 4	7 1	6 8	6 5	6 2	5 9		
	横方向 (A) 縦方向 (B)		3 . 0	8 2	7 7	7 3	7 0	8 0	7 6	7 2	6 9	7 7	7 3	7 0	6 7	7 3	7 0	6 8	6 5	6 2		
H m	1 . 3 0 H m	1 . 3 0 H m	4 . 0	8 4	8 1	7 7	7 4	8 2	7 9	7 6	7 3	7 9	7 6	7 4	7 1	7 6	7 4	7 1	6 9	6 6		
			5 . 0	8 6	8 3	8 0	7 7	8 4	8 1	7 9	7 6	8 1	7 8	7 6	7 4	7 8	7 6	7 4	7 2	6 8		
			7 . 0	8 8	8 5	8 3	8 1	8 6	8 4	8 2	8 0	8 3	8 1	7 9	7 7	7 9	7 8	7 7	7 5	7 2		
			1 0 . 0	8 9	8 7	8 6	8 4	8 7	8 6	8 4	8 3	8 4	8 3	8 1	8 0	8 1	8 0	7 9	7 8	7 4		

