

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 4 1
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176337 (0) DR 1
B Z 分類	B Z 3

器具効率		66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		1 % 65 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.67	0.6	41	34	29	26	40	34	29	26	39	33	29	26	37	32	28	26	25
			0.63	0.8	48	41	37	34	47	41	37	34	45	40	36	33	44	39	36	33	32
			1.0	52	46	42	39	51	46	42	39	49	45	41	38	48	44	41	38	37	
			0.56	1.25	56	51	47	44	55	50	46	43	53	49	46	43	51	48	45	43	41
下方投影面積		cm ²	1.5	58	54	50	47	57	53	49	47	55	52	49	46	53	50	48	46	44	
等価発光面積		cm ²	2.0	61	57	54	52	60	57	54	51	58	55	53	51	57	54	52	50	48	
取付 高さ	器具間隔最大限		2.5	63	60	57	55	62	59	57	54	60	58	55	53	58	56	54	53	51	
	横方向 (A) 縦方向 (B)		3.0	65	62	59	57	64	61	59	57	62	59	57	56	60	58	56	55	53	
H m	1.25 H m	1.25 H m	4.0	66	64	62	60	65	63	61	59	63	61	60	58	61	60	59	57	55	
			5.0	67	65	64	62	66	64	63	61	64	63	61	60	62	61	60	59	57	
			7.0	68	67	66	64	67	66	65	64	65	64	63	62	64	63	62	61	59	
			10.0	69	68	67	66	68	67	66	66	66	66	65	64	65	64	63	63	61	

