

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 4 1
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176338 (0) DR 1
B Z 分類	B Z 3

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	47	39	33	30	46	38	33	30	44	37	33	30	43	37	32	29	28
			0.63	0.8	55	47	42	38	54	47	42	38	52	46	41	38	50	45	41	38	36
			1.0	1.0	60	53	48	44	58	52	48	44	56	51	47	44	54	50	46	43	42
			0.56	1.25	64	58	53	50	62	57	53	49	60	56	52	49	58	54	51	48	47
下方投影面積		c m ²	1.5	66	61	57	53	65	60	56	53	63	59	55	52	61	57	54	52	50	
			2.0	70	65	62	59	69	65	61	58	66	63	60	58	64	61	59	57	55	
等価発光面積		c m ²	2.5 <td>72</td> <td>68</td> <td>65</td> <td>62</td> <td>71</td> <td>67</td> <td>64</td> <td>62</td> <td>69</td> <td>66</td> <td>63</td> <td>61</td> <td>66</td> <td>64</td> <td>62</td> <td>60</td> <td>58</td>	72	68	65	62	71	67	64	62	69	66	63	61	66	64	62	60	58	
			3.0	73	70	67	65	72	69	67	64	70	67	65	63	68	66	64	62	60	
H m	1.25 H m		1.25 H m	4.0	75	73	70	68	74	72	70	68	72	70	68	66	70	68	67	65	63
				5.0	76	74	72	71	75	73	71	70	73	71	70	69	71	70	68	67	65
				7.0	78	76	75	73	77	75	74	72	74	73	72	71	72	71	70	70	67
				10.0	79	78	76	75	78	77	76	75	76	75	74	73	74	73	72	71	69

