

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 4 1
光源	L L D 5 0 2 0 L C C 1 × 1 1 0 8 5 . 0 l m
管理番号	K 0 1 9 0 4 5 8 (1) D R 1
B Z 分類	B Z 1

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																Z C M	
下方光束		80 %																			
保守率		良	0 . 6 7	0 . 6	68	63	60	58	67	63	60	58	66	62	60	58	65	62	60	58	57
		中	0 . 6 3	0 . 8	73	69	66	64	72	68	66	64	71	68	65	64	70	67	65	63	63
		否	0 . 5 6	1 . 0	76	72	70	68	75	72	69	67	74	71	69	67	73	70	68	67	66
		1 . 2 5	78	75	73	71	77	74	72	71	76	74	72	70	75	73	71	70	69		
下方投影面積		c m ²	1 . 5	79	77	75	73	79	76	74	73	77	75	74	72	76	74	73	72	71	
			2 . 0	81	79	78	76	81	79	77	76	79	78	76	75	78	76	75	74	73	
取付高さ	器具間隔最大限		2 . 5	82	81	79	78	82	80	79	78	80	79	78	77	79	78	77	76	75	
	横方向 (A)	縦方向 (B)	3 . 0	83	82	81	79	82	81	80	79	81	80	79	78	79	79	78	77	76	
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	84	83	82	81	83	82	82	81	82	81	80	80	80	80	79	79	77	
			5 . 0	85	84	83	82	84	83	82	82	82	82	81	81	81	80	80	79	78	
			7 . 0	85	85	84	84	84	84	84	83	83	82	82	82	81	81	81	81	79	
			10 . 0	86	85	85	85	85	85	84	84	83	83	83	83	82	82	81	81	79	

