

屋内照明器具特性	
品番 (品名)	XLGB1012
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176325 (0) DR 1
BZ分類	BZ5 / 0.7 / BZ4 / 1.8 / BZ5

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		5 % 8 2 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	4 9	3 9	3 3	2 8	4 8	3 8	3 2	2 8	4 6	3 7	3 2	2 7	4 3	3 6	3 1	2 7	2 5
			0 . 6 3	0 . 8	5 8	4 8	4 2	3 7	5 7	4 8	4 1	3 7	5 4	4 6	4 0	3 6	5 1	4 5	4 0	3 6	3 4
			1 . 0	6 4	5 5	4 8	4 3	6 2	5 4	4 8	4 3	5 9	5 2	4 7	4 2	5 6	5 0	4 6	4 2	3 9	
			0 . 5 6	1 . 2 5	6 9	6 1	5 4	5 0	6 7	6 0	5 4	4 9	6 4	5 7	5 2	4 8	6 1	5 6	5 1	4 8	4 5
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 2	6 5	5 9	5 4	7 0	6 3	5 8	5 4	6 7	6 1	5 7	5 3	6 4	5 9	5 5	5 2	4 9	
			2 . 0	7 7	7 0	6 5	6 1	7 5	6 9	6 4	6 0	7 1	6 6	6 2	5 9	6 8	6 4	6 1	5 8	5 5	
取付高さ	器具間隔最大限		2 . 5	7 9	7 4	6 9	6 5	7 7	7 2	6 8	6 4	7 4	7 0	6 6	6 3	7 1	6 7	6 4	6 1	5 8	
	横方向 (A) 縦方向 (B)		3 . 0	8 1	7 6	7 2	6 8	7 9	7 5	7 1	6 7	7 6	7 2	6 9	6 6	7 3	7 0	6 7	6 4	6 1	
H m	1 . 2 9 H m 1 . 2 9 H m		4 . 0	8 4	8 0	7 6	7 3	8 2	7 8	7 5	7 2	7 9	7 5	7 3	7 0	7 5	7 3	7 0	6 8	6 5	
			5 . 0	8 5	8 2	7 9	7 6	8 3	8 0	7 7	7 5	8 0	7 7	7 5	7 3	7 7	7 5	7 3	7 1	6 7	
			7 . 0	8 7	8 4	8 2	7 9	8 5	8 3	8 1	7 8	8 2	8 0	7 8	7 6	7 9	7 7	7 6	7 4	7 1	
			1 0 . 0	8 8	8 6	8 4	8 3	8 7	8 5	8 3	8 1	8 4	8 2	8 1	7 9	8 1	7 9	7 8	7 7	7 3	

