

# 屋内照明器具特性

|         |                     |          |
|---------|---------------------|----------|
| 品番 (品名) | XLGB1013            |          |
| 光源      | LLD2000VCE1 ×1      | 531.0 lm |
| 管理番号    | K0176325(0)DR1      |          |
| BZ分類    | BZ5/0.7/BZ4/1.8/BZ5 |          |

|        |                  |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 87%              | 天井       | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|        | 上方光束<br>5%       |          | 下方光束<br>82%      | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 室指数    | 照明率 ( X0.01 )    |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率    | 良                | 0.67     | 0.6              | 4.9 | 3.9 | 3.3 | 2.8 | 4.8 | 3.8 | 3.2 | 2.8 | 4.6 | 3.7 | 3.2 | 2.7 | 4.3 | 3.6 | 3.1 | 2.7 | 2.5 |     |
|        | 中                | 0.63     | 0.8              | 5.8 | 4.8 | 4.2 | 3.7 | 5.7 | 4.8 | 4.1 | 3.7 | 5.4 | 4.6 | 4.0 | 3.6 | 5.1 | 4.5 | 4.0 | 3.6 | 3.4 |     |
|        | 否                | 0.56     | 1.0              | 6.4 | 5.5 | 4.8 | 4.3 | 6.2 | 5.4 | 4.8 | 4.3 | 5.9 | 5.2 | 4.7 | 4.2 | 5.6 | 5.0 | 4.6 | 4.2 | 3.9 |     |
|        |                  |          | 1.25             | 6.9 | 6.1 | 5.4 | 5.0 | 6.7 | 6.0 | 5.4 | 4.9 | 6.4 | 5.7 | 5.2 | 4.8 | 6.1 | 5.6 | 5.1 | 4.8 | 4.5 |     |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 7.2 | 6.5 | 5.9 | 5.4 | 7.0 | 6.3 | 5.8 | 5.4 | 6.7 | 6.1 | 5.7 | 5.3 | 6.4 | 5.9 | 5.5 | 5.2 | 4.9 |     |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 7.7 | 7.0 | 6.5 | 6.1 | 7.5 | 6.9 | 6.4 | 6.0 | 7.1 | 6.6 | 6.2 | 5.9 | 6.8 | 6.4 | 6.1 | 5.8 | 5.5 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 7.9 | 7.4 | 6.9 | 6.5 | 7.7 | 7.2 | 6.8 | 6.4 | 7.4 | 7.0 | 6.6 | 6.3 | 7.1 | 6.7 | 6.4 | 6.1 | 5.8 |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 8.1 | 7.6 | 7.2 | 6.8 | 7.9 | 7.5 | 7.1 | 6.7 | 7.6 | 7.2 | 6.9 | 6.6 | 7.3 | 7.0 | 6.7 | 6.4 | 6.1 |     |
| H m    | 1.29 H m         | 1.29 H m | 4.0              | 8.4 | 8.0 | 7.6 | 7.3 | 8.2 | 7.8 | 7.5 | 7.2 | 7.9 | 7.5 | 7.3 | 7.0 | 7.5 | 7.3 | 7.0 | 6.8 | 6.5 |     |
|        |                  |          | 5.0              | 8.5 | 8.2 | 7.9 | 7.6 | 8.3 | 8.0 | 7.7 | 7.5 | 8.0 | 7.7 | 7.5 | 7.3 | 7.7 | 7.5 | 7.3 | 7.1 | 6.7 |     |
|        |                  |          | 7.0              | 8.7 | 8.4 | 8.2 | 7.9 | 8.5 | 8.3 | 8.1 | 7.8 | 8.2 | 8.0 | 7.8 | 7.6 | 7.9 | 7.7 | 7.6 | 7.4 | 7.1 |     |
|        |                  |          | 10.0             | 8.8 | 8.6 | 8.4 | 8.3 | 8.7 | 8.5 | 8.3 | 8.1 | 8.4 | 8.2 | 8.1 | 7.9 | 8.1 | 7.9 | 7.8 | 7.7 | 7.3 |     |

