

屋内照明器具特性	
品番 (品名)	XLGB1508
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0175770 (0) DR1
BZ分類	BZ1/1.1/BZ2

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	45	39	36	33	44	39	35	33	43	38	35	33	42	38	35	33	32
			0.63	0.8	50	45	41	39	49	44	41	39	48	44	41	39	46	43	40	38	37
			0.56	1.0	53	49	45	43	52	48	45	43	51	47	44	42	49	46	44	42	41
				1.25	56	52	49	47	55	51	49	46	53	50	48	46	52	49	47	45	44
下方投影面積		cm ²		1.5	58	54	51	49	57	54	51	49	55	52	50	48	54	51	49	48	46
			等価発光面積	cm ²	2.0	60	57	55	53	59	56	54	52	57	55	53	52	56	54	52	51
取付 高さ	器具間隔最大限			2.5	62	59	57	55	61	58	56	55	59	57	55	54	57	56	54	53	51
	横方向 (A) 縦方向 (B)			3.0	63	60	59	57	62	60	58	56	60	58	57	56	58	57	56	55	53
H m	1.26 H m	1.26 H m		4.0	64	62	61	59	63	61	60	59	61	60	59	58	59	58	57	57	55
				5.0	65	63	62	61	64	62	61	60	62	61	60	59	60	59	59	58	56
				7.0	65	64	63	63	64	64	63	62	63	62	61	61	61	60	60	59	57
				10.0	66	65	65	64	65	64	64	63	63	63	62	62	62	61	61	60	58

