

屋内照明器具特性	
品番 (品名)	LGB15117
光源	LLD4000MLCE1 ×1 845.0 lm
管理番号	K0176310 (0) DR 1
BZ分類	BZ3

器具効率		70 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z CM
保守率		良 中 否	0.67	0.6	46	39	34	31	45	38	34	31	44	38	34	31	42	37	33	31	30				
			0.63	0.8	52	46	42	38	52	45	41	38	50	45	41	38	48	44	40	38	37				
			0.56	1.0	57	51	47	43	56	50	46	43	54	49	46	43	52	48	45	43	41				
				1.25	60	55	51	48	59	54	51	48	57	53	50	47	56	52	49	47	46				
下方投影面積		cm ²		1.5	63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49				
			等価発光面積	cm ²	2.0	66	62	59	56	65	61	58	56	63	60	57	55	61	59	56	54	53			
取付 高さ	器具間隔最大限			2.5	68	64	61	59	67	64	61	59	65	62	60	58	63	61	59	57	56				
	横方向 (A)		縦方向 (B)	3.0	69	66	64	61	68	65	63	61	66	64	62	60	64	63	61	59	58				
H m	1.39 H m		1.39 H m	4.0	70	68	66	64	70	67	66	64	68	66	64	63	66	65	63	62	60				
				5.0	71	70	68	66	71	69	67	66	69	67	66	65	67	66	65	64	62				
				7.0	73	71	70	69	72	70	69	68	70	69	68	67	68	67	67	66	64				
				10.0	73	72	72	71	73	72	71	70	71	70	69	69	69	69	68	67	65				

