

屋内照明器具特性	
品番 (品名)	LGB15117
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184504 (0) DR 1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			
下方光束		88 %		Z C M																			
保守率		良 中 否	0.67	0.6	76	72	69	67	76	72	69	67	75	71	68	67	74	71	68	66	66		
			0.63	0.8	81	77	74	72	80	76	74	72	79	76	73	71	78	75	73	71	70		
			0.56	1.0	84	80	77	75	83	79	77	75	82	79	76	75	80	78	76	74	73		
			1.25	86	83	80	78	85	82	80	78	84	81	79	77	82	80	78	77	76			
下方投影面積		c m ²	1.5	87	84	82	80	87	84	82	80	85	83	81	79	84	82	80	79	77			
			2.0	89	87	85	83	88	86	84	83	87	85	83	82	85	84	82	81	80			
取付高さ	器具間隔最大限		2.5	90	88	87	85	89	88	86	85	88	86	85	84	86	85	84	83	81			
	横方向 (A)	縦方向 (B)	3.0	91	89	88	86	90	89	87	86	88	87	86	85	87	86	85	84	82			
H m	0.77 H m	0.77 H m	4.0	92	91	89	88	91	90	89	88	89	88	87	86	88	87	86	85	83			
			5.0	93	92	90	89	92	91	90	89	90	89	88	87	88	87	87	86	84			
			7.0	93	93	92	91	92	92	91	90	91	90	89	89	89	88	88	87	85			
			10.0	94	93	93	92	93	92	92	91	91	91	90	90	89	89	88	88	86			

