

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 1 7
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 l m
管理番号	K 0 1 9 0 4 2 8 (0) D R 1
B Z 分類	B Z 2

器具効率		9 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		0 % 9 2 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	6 2	5 3	4 7	4 3	6 1	5 2	4 7	4 3	5 9	5 1	4 6	4 3	5 7	5 1	4 6	4 3	4 1	
			0 . 6 3	0 . 8	7 1	6 3	5 8	5 4	7 0	6 3	5 7	5 4	6 8	6 2	5 7	5 3	6 6	6 1	5 6	5 3	5 2	
			1 . 0	7 7	7 0	6 5	6 1	7 6	6 9	6 4	6 1	7 4	6 8	6 4	6 0	7 2	6 7	6 3	6 0	5 8		
			0 . 5 6	1 . 2 5	8 1	7 5	7 1	6 7	8 0	7 5	7 0	6 7	7 8	7 3	6 9	6 6	7 6	7 2	6 9	6 6	6 4	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 4	7 9	7 4	7 1	8 3	7 8	7 4	7 1	8 1	7 7	7 3	7 0	7 9	7 5	7 2	7 0	6 8		
			2 . 0	8 8	8 4	8 0	7 7	8 7	8 3	7 9	7 6	8 5	8 1	7 8	7 6	8 3	8 0	7 7	7 5	7 3		
取付 高さ	器具間隔最大限		2 . 5	9 1	8 7	8 3	8 1	8 9	8 6	8 3	8 0	8 7	8 4	8 2	7 9	8 5	8 3	8 0	7 8	7 6		
	横方向 (A)	縦方向 (B)	3 . 0	9 2	8 9	8 6	8 3	9 1	8 8	8 5	8 3	8 9	8 6	8 4	8 2	8 7	8 4	8 3	8 1	7 9		
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	9 4	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 1	8 9	8 7	8 5	8 9	8 7	8 5	8 4	8 2		
			5 . 0	9 5	9 3	9 1	8 9	9 4	9 2	9 0	8 9	9 2	9 0	8 9	8 7	9 0	8 8	8 7	8 6	8 4		
			7 . 0	9 6	9 5	9 3	9 2	9 5	9 4	9 3	9 1	9 3	9 2	9 1	9 0	9 1	9 0	8 9	8 8	8 6		
			1 0 . 0	9 7	9 6	9 5	9 4	9 6	9 5	9 4	9 3	9 4	9 3	9 2	9 2	9 2	9 1	9 1	9 0	8 8		

