

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | LGB15117                |
| 光源       | LLD4000LCT1 ×1 845.0 lm |
| 管理番号     | K0190513 ( 0 ) DR 1     |
| BZ分類     | BZ3                     |

| 器具効率     |                     | 71 %            | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.67   | 0.6             | 47                | 39 | 35 | 32 | 46   | 39 | 35 | 31 | 44   | 38 | 34 | 31 | 43   | 38 | 34 | 31 | 30  |
|          |                     |                 | 0.63   | 0.8             | 53                | 47 | 42 | 39 | 52   | 46 | 42 | 39 | 51   | 45 | 42 | 39 | 49   | 45 | 41 | 39 | 37  |
|          |                     |                 | 0.56   | 1.0             | 58                | 52 | 47 | 44 | 57   | 51 | 47 | 44 | 55   | 50 | 47 | 44 | 53   | 49 | 46 | 43 | 42  |
|          |                     |                 |        | 1.25            | 61                | 56 | 52 | 49 | 60   | 55 | 52 | 49 | 58   | 54 | 51 | 48 | 57   | 53 | 50 | 48 | 47  |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5             | 64                | 59 | 55 | 52 | 63   | 58 | 55 | 52 | 61   | 57 | 54 | 51 | 59   | 56 | 53 | 51 | 50  |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 67 | 63 | 60 | 57   | 66 | 62 | 59 | 57   | 64 | 61 | 58 | 56   | 62 | 60 | 57 | 55  |
| 取付<br>高さ | 器具間隔最大限             |                 |        | 2.5             | 69                | 65 | 63 | 60 | 68   | 65 | 62 | 60 | 66   | 63 | 61 | 59 | 64   | 62 | 60 | 58 | 57  |
|          | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 70                | 67 | 65 | 63 | 69   | 66 | 64 | 62 | 67   | 65 | 63 | 61 | 66   | 64 | 62 | 60 | 59  |
| H m      | 1.39 H m            | 1.39 H m        |        | 4.0             | 72                | 69 | 67 | 66 | 71   | 69 | 67 | 65 | 69   | 67 | 66 | 64 | 67   | 66 | 64 | 63 | 61  |
|          |                     |                 |        | 5.0             | 73                | 71 | 69 | 68 | 72   | 70 | 69 | 67 | 70   | 69 | 67 | 66 | 68   | 67 | 66 | 65 | 63  |
|          |                     |                 |        | 7.0             | 74                | 73 | 71 | 70 | 73   | 72 | 71 | 69 | 71   | 70 | 69 | 68 | 70   | 69 | 68 | 67 | 65  |
|          |                     |                 |        | 10.0            | 75                | 74 | 73 | 72 | 74   | 73 | 72 | 71 | 72   | 71 | 71 | 70 | 70   | 70 | 69 | 69 | 67  |

