

屋内照明器具特性

品番 (品名)	S C 4 2 7	
光源	LDA4L-G-E17/Z40E/S/W/2 x1	440.0 l m
管理番号	K0157700(0)DB1	
BZ分類	BZ9	

器具効率	92%	天井	80%					70%					50%					30%					0%	
	上方光束		57%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		35%	壁	10%					10%					10%					10%				
室指数	照明率 (X0.01)																							ZCM
保守率	良	0.63	0.6	0.56	0.6	40	29	22	17	36	26	20	15	28	21	16	12	21	16	12	9	4		
	中	0.6	0.6	0.6	0.6	48	37	29	24	43	33	27	22	34	26	21	17	25	20	16	13	6		
	否	0.56	0.56	0.56	0.56	53	43	35	30	48	39	32	27	38	31	26	22	28	23	19	16	8		
下方投影面積	c m ²		1.25	1.5	2.0	58	48	41	35	52	44	37	32	41	35	30	26	31	27	23	20	10		
	等価発光面積		c m ²	2.0	2.5	62	53	46	40	56	48	42	36	44	38	33	29	34	29	26	23	12		
取付高さ	器具間隔最大限		2.5	3.0	4.0	70	63	57	52	64	57	52	48	51	46	42	39	39	36	33	30	17		
	横方向 (A)	縦方向 (B)	3.0	4.0	5.0	73	66	61	56	66	60	56	51	53	49	45	42	41	38	35	32	18		
H m	0.00H m	0.00H m	4.0	5.0	7.0	76	71	66	62	69	64	60	57	55	52	49	46	43	40	38	36	21		
			5.0	7.0	10.0	78	73	69	66	71	67	63	60	57	54	52	49	45	42	40	38	23		
			7.0	10.0	80	77	73	70	73	70	67	65	59	57	55	53	47	45	43	42	42	25		
			10.0		82	79	77	75	75	73	70	68	61	59	58	56	48	47	46	44	44	27		

