

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 3 7
光源	LLD4000LCT1 ×1 845.0 l m
管理番号	K0190513 (0) DR 1
B Z 分類	B Z 3

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	47	39	35	32	46	39	35	31	44	38	34	31	43	38	34	31	30
			0.63	0.8	53	47	42	39	52	46	42	39	51	45	42	39	49	45	41	39	37
			0.56	1.0	58	52	47	44	57	51	47	44	55	50	47	44	53	49	46	43	42
				1.25	61	56	52	49	60	55	52	49	58	54	51	48	57	53	50	48	47
下方投影面積		c m ²		1.5	64	59	55	52	63	58	55	52	61	57	54	51	59	56	53	51	50
			等価発光面積	2.0	67	63	60	57	66	62	59	57	64	61	58	56	62	60	57	55	54
取付 高さ	器具間隔最大限			2.5	69	65	63	60	68	65	62	60	66	63	61	59	64	62	60	58	57
	横方向 (A)	縦方向 (B)		3.0	70	67	65	63	69	66	64	62	67	65	63	61	66	64	62	60	59
H m	1.39 H m	1.39 H m		4.0	72	69	67	66	71	69	67	65	69	67	66	64	67	66	64	63	61
				5.0	73	71	69	68	72	70	69	67	70	69	67	66	68	67	66	65	63
				7.0	74	73	71	70	73	72	71	69	71	70	69	68	70	69	68	67	65
				10.0	75	74	73	72	74	73	72	71	72	71	71	70	70	70	69	69	67

