

屋内照明器具特性

品番 (品名)	XLY120HYL									
光源	LED3000_85_2640 x1					2640.0 lm				
管理番号	K0155408(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	6%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	94%																																																						
保守率	良 中 否	0.83	0.6	5.4	4.2	3.4	2.8	5.3	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.7	3.8	3.2	2.7	2.5																																			
		0.81	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.8	5.8	4.9	4.2	3.7	5.5	4.7	4.1	3.6	3.3																																			
		0.77	1.0	7.0	5.9	5.1	4.5	6.8	5.8	5.0	4.4	6.4	5.5	4.9	4.4	6.1	5.3	4.7	4.3	4.0																																			
			1.25	7.6	6.6	5.8	5.2	7.4	6.5	5.7	5.2	7.0	6.2	5.6	5.0	6.6	5.9	5.4	4.9	4.6																																			
下方投影面積	c m ²	1.5	8.0	7.1	6.3	5.8	7.8	6.9	6.2	5.7	7.4	6.6	6.1	5.6	7.0	6.4	5.9	5.4	5.1																																				
		2.0	8.6	7.8	7.1	6.6	8.4	7.6	7.0	6.5	7.9	7.3	6.8	6.3	7.5	7.0	6.6	6.2	5.8																																				
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.3	7.8	7.3	6.9	7.9	7.4	7.0	6.7	6.3																																			
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.6	9.0	8.4	7.9	7.5	8.6	8.1	7.7	7.3	8.2	7.8	7.4	7.1	6.7																																			
1.5m	2m	2.13m	4.0	9.5	9.0	8.6	8.2	9.3	8.9	8.4	8.1	8.9	8.5	8.2	7.8	8.5	8.2	7.9	7.6	7.2																																			
2	2.63	2.69	5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.1	8.8	8.5	8.2	8.7	8.5	8.2	8.0	7.5																																			
2.5	3.28	3.27	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.4	9.1	8.9	8.7	9.0	8.8	8.6	8.4	7.9																																			
3	3.91	3.87	10.0	10.2	9.9	9.7	9.5	10.0	9.8	9.5	9.3	9.6	9.4	9.2	9.0	9.2	9.0	8.9	8.8	8.3																																			

