

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 3 6
光源	LLD5000LCC1 ×1 1140.0 l m
管理番号	K0190425 (0) DR 1
B Z 分類	B Z 2

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	60	51	46	42	59	51	46	42	57	50	46	42	56	50	45	42	41
			0.63	0.8	69	61	56	52	68	60	56	52	66	59	55	52	64	59	55	52	50
			0.56	1.0	74	67	62	58	73	66	62	58	71	65	61	58	69	64	61	58	56
				1.25	78	72	68	64	77	71	67	64	75	70	66	63	73	69	66	63	61
下方投影面積		c m ²		1.5	81	75	71	68	80	75	71	68	77	73	70	67	76	72	69	66	65
			等価発光面積	c m ²	2.0	84	80	76	73	83	79	76	73	81	78	75	72	79	76	74	72
取付 高さ	器具間隔最大限			2.5	87	83	80	77	85	82	79	76	83	80	78	76	81	79	77	75	73
	横方向 (A)		縦方向 (B)	3.0	88	85	82	80	87	84	81	79	85	82	80	78	83	81	79	77	75
H m	1.29 H m		1.29 H m	4.0	90	87	85	83	89	86	84	82	87	85	83	81	85	83	81	80	78
				5.0	91	89	87	85	90	88	86	85	88	86	85	83	86	84	83	82	80
				7.0	92	91	89	88	91	90	88	87	89	88	87	86	87	86	85	84	82
				10.0	93	92	91	90	92	91	90	89	90	89	88	88	88	87	87	86	84

