

屋内照明器具特性	
品番 (品名)	LGB15336
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190525 (0) DR 1
BZ分類	BZ3

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	46	39	35	31	46	39	34	31	44	38	34	31	43	38	34	31	30
			0.63	0.8	53	46	41	38	52	45	41	38	50	45	41	38	48	44	40	38	36
			0.56	1.0	57	50	46	43	56	50	46	42	54	49	45	42	52	48	45	42	41
				1.25	60	54	50	47	59	54	50	47	57	53	49	46	55	52	49	46	45
下方投影面積		cm ²		1.5	62	57	53	50	61	57	53	50	59	55	52	50	58	54	52	49	48
			等価発光面積	cm ²	2.0	66	61	58	55	65	61	58	55	63	59	57	54	61	58	56	54
取付 高さ	器具間隔最大限			2.5	68	64	61	58	67	63	61	58	65	62	60	57	63	61	59	57	55
	横方向 (A) 縦方向 (B)			3.0	69	66	63	61	68	65	63	61	66	64	62	60	64	62	61	59	57
H m	1.32 H m	1.32 H m	4.0	71	68	66	64	70	68	66	64	68	66	64	63	66	65	63	62	60	
			5.0	72	70	68	66	71	69	67	66	69	68	66	65	67	66	65	64	62	
			7.0	73	72	70	69	72	71	70	68	70	69	68	67	69	68	67	66	64	
			10.0	74	73	72	71	73	72	71	70	71	71	70	69	70	69	68	68	66	

