

屋内照明器具特性

| | | |
|---------|--------------------|-----------|
| 品番 (品名) | XND1031SW | |
| 光源 | LED4000_85_1040 x1 | 1040.0 lm |
| 管理番号 | K0158704(0)DB1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 0% | | 下方光束 100% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.81 | 0.6 | 73 | 64 | 58 | 54 | 72 | 63 | 58 | 54 | 70 | 63 | 58 | 54 | 68 | 62 | 57 | 54 | 53 | |
| | 中 | 0.77 | 0.8 | 82 | 74 | 69 | 65 | 81 | 74 | 69 | 65 | 79 | 73 | 68 | 65 | 77 | 72 | 68 | 65 | 63 | |
| | 否 | 0.68 | 1.0 | 88 | 81 | 76 | 73 | 87 | 80 | 76 | 73 | 85 | 79 | 75 | 72 | 83 | 78 | 75 | 72 | 70 | |
| | | | 1.25 | 92 | 86 | 82 | 79 | 91 | 86 | 82 | 79 | 89 | 84 | 81 | 78 | 87 | 83 | 80 | 78 | 76 | |
| 下方投影面積 | cm ² | | 1.5 | 95 | 90 | 86 | 83 | 94 | 89 | 85 | 82 | 92 | 88 | 84 | 82 | 90 | 86 | 84 | 81 | 79 | |
| 等価発光面積 | cm ² | | 2.0 | 99 | 94 | 91 | 88 | 97 | 94 | 91 | 88 | 95 | 92 | 89 | 87 | 93 | 90 | 88 | 86 | 84 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 101 | 97 | 94 | 92 | 99 | 96 | 94 | 91 | 97 | 95 | 92 | 90 | 95 | 93 | 91 | 89 | 87 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 102 | 99 | 97 | 94 | 101 | 98 | 96 | 94 | 99 | 96 | 94 | 93 | 97 | 95 | 93 | 92 | 89 | |
| Hm | 1.12Hm | 1.12Hm | 4.0 | 104 | 101 | 99 | 98 | 103 | 100 | 99 | 97 | 100 | 99 | 97 | 96 | 98 | 97 | 95 | 94 | 92 | |
| | | | 5.0 | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99 | 101 | 100 | 99 | 97 | 99 | 98 | 97 | 96 | 94 | |
| | | | 7.0 | 106 | 105 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 100 | 99 | 99 | 98 | 95 | |
| | | | 10.0 | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 97 | |

